Form approved. Budget Bureau No. 42-B1425.

5. LEASE DESIGNATION AND BERIAL NO.

UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY USA-U-13252 6. IF INDIAN, ALLOTTER OR TRIBE NAME APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 1a. TYPE OF WORK 7. UNIT AGEREMENT NAME DRILL 🛛 DEEPEN PLUG BACK b. TYPE OF WELL BINGLE X MULTIPLE CONE WELL X WELL S. FARM OR LEASE NAME OTREE 2. NAME OF OPERATOR BURR DESERT Southland Royalty Company 9. WELL NO. 3. ADDRESS OF OPERATOR P. O. Drawer 570, Farmington, New Mexico 87401 NI ACHT 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*) 1990' FNL & 750' FEL SE NE 11. SEC., T., E., M., OB BLE. AND SURVEY OR AREA At proposed prod. sone Sec. 24, T30S, RIZE Same 14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE® 18.7 miles southeast of Hanksville, Utah

10. DISTANCE FROM PROPOSED*
LOCATION TO MEAREST
PROPERTY OR LEASE LINE, FT.
(Also to nearest drig. unit line, if any)

1990' Utah Wayne 16. NO. OF ACRES IN LEASE 17. NO. OF ACRES ASSIGNED 2560 18. DISTANCE FROM PROPOSED LOCATIONS 19. PROPOSED DEPTH 20. ROTARY OR CABLE TOOLS TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR ON THIS LEASE, FT. N/A 6700 \L\\ Rotary 21. ELEVATIONS (Show whether DF, RT, GR, etc.) 22. APPROX. DATE WORK WILL START* 5165' GR October 15, 1979 23. PROPOSED CASING AND CEMENTING PROGRAM QUANTITY OF CEMENT WEIGHT PER FOOT SETTING DEPTH BIZE OF BOLE SIZE OF CASING <u> 200'</u> 17 1/2" 13 3/8" New 48#,H-40,ST&C 235 sx Cl B w/3% CaCl. 12 1/4" *8 5/8" New 24#,K-55,ST&C 3000 325 sx Cl B w/additives 6700' 7/8" 5 1/2" 14#,K-55,ST&C 900 sx Cl B 50/50 Poz w/adds. New Drill 17 1/2" surface hole and set 13 3/8" surface casing to 200' with good returns. 1. Log BOP Checks in daily drilling reports and drill 12 1/4" hole to 3000'. 2. Run logs and run 8 5/8" casing only if lost circulation has occured. 3. Run logs and run 5 1/2" casing if productive. 4. Run other logs as needed and perforate and stimulate as needed. 6. Exhibits Attached "H" Drill Rig Layout Location and Elevation Plat DIVISION OF OIL "J" Rehabilitation Plan "B" The Ten-Point Compliance Program GAS, & MINING "K" Fracturing Program "C" The Blowout Preventer Diagram "D" The Multi-Point Requirements for A. P. D. "E&E₁" Access Road Map Into Location "F" Radius Map of Field Drill Pad Layout & Cut - Fill Section, Production Facilities IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any. District Production Manager BIGNED (This space for Federal or State office use) PERMIT NO. CONDITIONS OF APPROVAL, IF ANY:

EXHIBIT "A"

LOCATION AND ELEVATION PLAT

COMPANY	, SOUTHI	AND ROYAL	TY COMPANY	
LEASE	BURR I	DESERT	WELL N	o. <u>1</u>
\$EC	2 <u>4</u> , т.	308	, <u>n12E</u>	
LOCATION		COUNTY, U		
ELEVATION 5165 ungraded ground				
		.]		
<u> </u>	- +	- 	 	
		1	1	13900
		 		750
,		Se c.		• •
1		, 	2h I	. 1
1	.]	1	1	
1			1	
+				1
CALE-4 I	CHES EQ	JALS 1 MILE		
TELD NOTE	OF ACTU	AL SURVEYS	OVE PLAT WAS F MADE BY ME UN E TRUE AND CO LIEF.	DER MY SUPER-
		Fred I	Kerr Jr.	2
EAL:		#3950	Registered Land St	irveyor,
URVEYED	Augi	ist 20		1 9 79

EXHIBIT "B"

TEN-POINT COMPLIANCE PROGRAM OF NIL-6 APPROVAL OF OPERATIONS

Attached to Form 9-331C

SOUTHLAND ROYALTY COMPANY #1 Burr Desert - Federal 1190' FNL & 750' FEL, Sec. 24, T30S, R12E Wayne County, Utah

1. The Geologic Surface Formation

The surface formation is Entrada.

2. Estimated Tops of Important Geological Markers

Wingate	1240'	Penn	4250'
_		·	
Chinle	1530 '	Ismay	4600'
Moenkopi	1825'	Paradox	7425'
Kaibab	2260'	Molas.	5340 '
White Rim	2 2 75 '	Miss	5460 '
Organ Rock	2735 '	Devoian	6190'
Cedar Mesa	2945 '	McCracken	6540' 🛩
Elephant Canyon	3790'		

3. Estimated Depths of Anticipated Water, Oil, Gas or Minerals

Navajo 400' Water Pennsylvanian 4250' Oil & Gas

4. The Proposed Casing Program

- (a) Surface Casing: Set 13 3/8", new H-40, 48#, ST & C, at 200' in 17 1/2" hole; cement with 235 sacks of Class "B" with 3% CaCl₂ (100% excess to circulate cement to surface).
- (b) Intermediate Casing: (to be run only if lost circulation occurs)
 Set 8 5/8", new K-55, 24#, ST & C at 3000' in 12 1/4" hole; cement
 with 255 sacks of 50/50 Class "B" poz with 6% gel and 1/4# cello
 flake per sack. Tail in with 70 sacks of Class "B" cement with 2%
 CaCl₂ (50% excess to cover White Rim).
- (c) Production Liner: Set 5 1/2", new K-55, 14#, ST & C at 6700' in a 7 7/8" hole; cement with 900 sacks 50/50 Class "B" poz with 6% gel and .6% Halad 9 and 1/4# gel flake per sack (100% excess to circulate liner).

5. The Operator's Minimum Specifications for Pressure Control

EXHIBIT "C" is a schematic diagram of the blowout preventer equipment. The BOP's will be hydraulically tested to the full working pressure after nippling up and after any use under pressure. Pipe rams will be operationally checked each 24-hour period, as will blind rams and annular preventer each time pipe is pulled out of hole. Such checks of the BOP will be noted on daily drilling reports.

Accessories to BOP will include an upper and lower kelly cock, floor safety valve, drill string BOP and chock manifold with pressure rating equivalent to the BOP stack.

6. The Type and Characteristics of the Proposed Circulating Muds

This well will be drilled with fresh water, low solids mud from surface to total depth. Exhasust will be muffled. Other materials will be on site to handle any anticipated downhole problems as well as possible spill of fluids on the surface.

7. The Auxiliary Equipment to be Used

- (a) A kelly cock will be kept in the string at all times.
- (b) A float will be used at the bit at all times.
- (c) A mud logging unit and gas detecting device will be monitoring the system.
- (d) A stabbing valve will be on the floor to be stabbed into the drill pipe when kelly is not in the string.

8. The Testing, Logging and Coring Programs to be Followed

- (a) Will test all shows below 3500'.
- (b) The logging program will consist of BHC Sonic, FDC/CNL with caliper, SP DIL and GR. Other logs will be determined at well site to best evaluate any shows.
- (c) Anticipate coring 270' selectively thru the Paradox.
- (d) Completion will be determined after review of logs and tests

9. Any Anticipated Abnormal Pressures or Temperatures


No abnormal pressures or temperatures have been noted or reported in wells drilled in the area nor at the depths anticipated in this well.

No hydrogen sulfide or other hazardous fluids or gases have been found, reported or known to exist at these depths in the area.

10. Anticipated Starting Date and Duration of the Operations

The anticipated starting date is set for November 1, 1979, or as soon as possible after examination and approval of drilling requirements. Operations should be completed within 30 days after spudding well and drilling to casing point.

EXHIBIT "C" BLOWOUT PREVENIER DIAGRAM



Preventers and spools are to have through bore of 6" - 3000# PSI or larger.

EXHIBIT "D"

MULTI-POINT REQUIREMENTS TO ACCOMPANY A.P.D.

Attached to Form 9-331C

#1 Burr Desert - Federal Section 24, T30S, R12E 1990' FNL & 750' FEL Wayne County, Utah

1. Existing Roads

- A. The proposed well site and elevation plat is shown as EXHIBIT "A".
- B. The distance from Hanksville, Utah is 15.5 miles. Proceed South 15.5 miles on highway 95; thence left 3.2 miles on Dell Seep Road; thence left 2.5 miles North of Dell Seep Road to location, as shown on EXHIBIT "E.
- C. All roads are color-coded into location, as shown on EXHIBIT "E₁".
- D. N/A.
- E. This is an exploration well. All existing roads within a two-mile radius are shown on EXHIBIT "E".
- F. 3.6 miles of Dell Seep road will need only minor improvements.

 2.5 miles of seismic trail form Dell Seep road to location will be upgraded to 20' road bed. Maintenance will be performed as required.

2. Planned Access Roads

Map showing all necessary access roads to be constructed or reconstructed is shown as EXHIBIT "E," for the following

- (1) The maximum width of the running surface of the access road will be 20'.
- (2) Grade will be less than 8% on all roads.
- (3) No turn outs are planned.
- (4) Appropriate water bars will be constructed to assure drainage off location to conform with the natural drainage pattern and off road bed.
- (5) No culverts are planned, however, they will be installed at two wash crossings if necessary. No major cut or fills are anticipated along access road during drilling operations.
- (6) Surfacing material will be native soil.
- (7) No gates, cattle guards or fence cuts are needed.

EXHIBIT "D" #1 Burr Desert

(8) The new access road to be built has been staked during the time of staking the location, as is centerline as shown on EXHIBIT "E,".

3. Location of Existing Wells

For all existing wells within a one-mile radius of this exploration well see EXHIBIT "F".

- (1) There are no water wells within a one-mile radius of this location.
- (2) There are no abandon wells in this one mile radius.
- (3) There are no temporarily abandoned wells.
- (4) There are no disposal wells.
- (5) There are no wells presently being drilled.
- (6) There are no producing wells within this one-mile radius.
- (7) There are no shut in wells.
- (8) There are no injection wells.
- (9) There are no monitoring or observation wells for other uses.

4. Location of Existing and/or Proposed Facilities

- A. Within a one-mile radius of location the following existing facilities are owned or controlled by lessee/operator:
 - (1) Tank Batteries: None
 - (2) Production Facilites: None
 - (3) Oil Gathering Lines: None
 - (4) Gas Gathering Lines: None
 - (5) Injection Lines: None
 - (6) Disposal Lines: None
- B. If production is obtained, new facilities will be as follows:
 - (1) Production facilities will be located on solid ground of cut area of drill pad, as shown on EXHIBIT "G".

- (2) All well flow lines will be burried and will be on the well site and production site.
- (3) Facilities will be 300 feet long and 150 feet wide.
- (4) All construction materials for condensate storage site and pad will be obtained from site. No additional material from outside sources is anticipated.
- (5) Any necessary pits will be fenced and flagged to protect livestock and wildlife.
- C. Rehabilitation, whether well is productive or dry, will be made on all unused areas in accordance with the restoration plans presented in ITEM #10 following.

5. Location and Type of Water Supply

- A. The source of water will be the Fremont River at Hanksville.
- B. Water will be transported by truck over existing roadways.
- C. No water well is to be drilled on this lease.

6. Construction Materials

- A. No Construction materials are needed for drilling or access roads into the drilling location unless production is obtained. The surface soil materials will be sufficient or will be purchased from the Dirt Contractor as needed.
- B. No construction materials will be taken off this Federal land.
- C. All surface soil materials for construction of access roads are sufficient.
- D. All major access roads presently exist as shown on EXHIBIT "E".

7. Handling of Waste Materials and Disposal

- (1) Drill cuttings will be burried in the reserve pit and covered.
- (2) Drilling fluids will be handled in the reserve pit.
- (3) Any fluids produced during drilling test or while making production test will be collected in a test tank. If a test tank is not available during drilling, fluids will be handled in reserve pit. Any spills of oil, gas, salt waters or other noxious fluids will be cleaned up and removed.
- (4) Chemical facilities will be provided for human waste.

- (5) Garbage and non-flammable waste and salts and other chemicals produced during drilling or testing will be handled in trash pit. Flammable waste will be disposed of in burn pit. Drill fluids, water, drilling mud and tailings will be kept in reserve pit, as shown on EXHIBIT "H".
- (6) After the rig moves out, all materials will be cleaned up and no adverse materials will be left on location. Any dangerous open pit will be fenced during drilling and kept closed until such time as the pit is leveled. Reserve pit will be fenced on three sides and the fourth side fenced upon removal of the rig. The trash and or burn pit will be totally enclosed with small mesh wire.

Ancillary Facilities

No air strip, camp or other facilities will be built during drilling of this well.

9. Well Site Layout

- (1) EXHIBIT "G" is the Drill Pad Layout as staked, with elevations, by Kerr Land Survey of Farmington, New Mexico. Cuts and fills have been drafted to visualize the planned cut across the location spot and to the deepest part of the pad. Topsoil will be stockpiled per BLM specifications determined at time of predrill inspection.
- (2) EXHIBIT "H" is a plan diagram of the proposed rig and equipment, reserve pit, burn and trash pit, pipe racks and mud tanks. No permanent living facilities are planned. There will be a trailer on site.
- (3) EXHIBIT "G" includes a diagram showing the proposed production facilities layout.
- (4) The reserve pits will not be lined. Steel mud tanks may be used during drilling operations.

10. Plans for Restoration

Location will be rehabilitated according to BLM specifications as soon as drilling operations have been completed.

11. Other Information

(1) The soil is blow sand. No distinguishing geological features are present. The area is covered with sparse scrub vegetation. Primary wildlife are rabbits and coyotes. The topography is gently rolling northward dip.

- (2) The primary surface use is grazing. The surface is owned by the United States Government.
- (3) The closest live water is the Dirty Devil River located 5 miles East of location, as shown on EXHIBIT "E".

The closest occupied dwellings are 7 miles West of the proposed location, as shown on EXHIBIT "E".

There are no known archaeological, historical or cultural heritages that will be disturbed by this drilling.

- (4) There are no reported restrictions or reservations noted on the oil and gas lease.
- (5) Drilling is planned for, on, or about October 15, 1979. It is anticipated that the final casing point will be reached within 30 days after commencement of drilling.

12. Lessee's or Operator's Representative

L. O. Van Ryan Southland Royalty Company P. O. Box 570 Farmington, New Mexico Phone (505) 325-1841

13. Certification

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route; that I am familiar with the conditions which presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and, that the work associated with the operations proposed herein will be performed by Southland Royalty Company and it's contractors and subcontractos in conformity with this plan and the terms and conditions under which it is approved.

Date

L. O. Van Ryan

District Production Manager Southland Royalty Company

EXHIBIT "J"

REHABILITATION PLAN

Lease No: U132	52	; Well Name & No: BURR DESERT #1
Iocation: 199	0' FNL & 75	0' FEL , Sec. 24 ,T 30S,R 12E
Southland	Rovalty Cor	mpany intends to drill a well on
surface owned b	v Bureau	of Land Management . The lesee/operator
agrees to compl	ete the fol	intends to drill a well on of Land Management. The lesee/operator lowing rehabilitation work if the well is a producer:
Yes	No	Maintain access road and provide adequate drainage to road.
XYes	No	Reshape and reseed any area not needed for maintenance of the pump and support facilities.
Other requirement	nts:	None
The following wo	ork will be	completed when the well is abandoned:
XYes	No	Pit will be fenced until dry, then filled to conform to surrounding topography.
X Yes	No	Water bars will be constructed as deemed necessary.
X Yes	No	Site will require reshaping to conform to surrounding topography.
X Yes	No No	Entire disturbed area will be reseeded. If yes, the following seed mixture will be used:
XYes	No	Access road will be closed, rehabilitated and reseeded using the same seed mixture as above.
Yes	X No	Access road will remain for surface owner's use.
XYes	No No	Water bars will be constructed on the access road as deemed necessary.
Other requirement	s:	None
Surface Owner:		Operator/Lessee
Name: Bureau of	Land Manag	ement Name: Southland Royalty Company
Address: Henry Mou	ntain Resou	
City: Hanksvill		City: Farmington
State: Utah		State: New Mexico
Telephone:		Telephone: (505) 325-1841
Date:		Date: 9-27-79
I CERTIFY rehabili	tation has	been discussed with me, the surface owner:
		N/A
		(Surface Owner's Signature)

This plan covers rehabilitation requirements only and does not affect any other agreements between the lessee/operator and surface owner.

ARECREATION AREA





EXHIBIT "E1" BULL MOUNTAIN QUADRANGLE ACCESS ROAD TO LOCATION UTAH 15 MINUTE SERIES (TOPOG SOUTHLAND ROYALTY COMPANY #1 BURR DESERT 1990' FNL & 750' FEL, Sec. 24, T30 S, R12E WAYNE COUNTY, UTAH 23 Ε 29 East Gale Reservoir 33 35 Oil Road Gravel Road Existing Road New Access Rd. Vicinity Map for SOUTHLAND ROYALTY CO. #1 BURR DESERT 1990'FNL 750'FEL Sec 24-T30S-R12E WAYNE COUNTY, UTAH

LALILUAT F



SOUTHLAND ROYALTY COMPANY #1 BURR DESERT 1990'FNL 750'FEL Sec 24-T308-R12E WAYNE COUNTY, UTAH 00 EXHIBIT "H" DRILL RIG LAYOUT STOCK PILES Access PIPE RACKS RIG £29°35'5 CZP **...** Cza TKASH BI Vert. 1"=40" Heriz: 1 = 100' Reserve C-C' Horiz: 1'= 100' Vert: 1'540' 5/70 Pit 5160 FI2 8-B' D-0' 5170 5160 KERR LAND SURVEYING Date: 8/20/79

POCKLION BROLITE 1 ---

1990'FNL 750'FEL Sec 24-T30S-R12E WAYNE COUNTY, UTAH WATER 00 Sand Binz Blenden EXHIBIT "K" FRACTURING PROGRAM LAYOUT Pump Trucks A. 0 175' -CZQ Ground Elay. 5165 Gradul Elav. 5163 Cze انق Vert. 1"=40" Heri'z: 1"= 100' Hariz: 1'= 100' Reserve Vert: 1's 40' c-c' 5170 Pit teece 5160 5150 FIC 8-8' D-0' 5170 5160 5150

SOUTHLAND ROYALTY CO. #1 BURK DESERT

KERR LAND SURVEYING Date: August 20, 1979

ftle no**tation**s

tered in NID File		Checked by Chief Approval Letter Disapproval Letter
COMPLETION DATA:	2.22.30	Location Inspected
W TA OS PA		Bond released State of Fee Land
priller's Log Electric Logs (20.)	Loss Trues	
BHC Sonic GR CCLog.	. lat M-L	Sonic

** FILE NOTATIONS ** DATE: October 5, 1979 Operator: South land Royalty Company
Well No: Burn Desert #1
Location: Sec. 24 T. 305 R. 12 E County: Wayne File Prepared: Entered on N.I.D.: Card Indexed: / /] Completion Sheet: [] API Number 43-055-30026 CHECKED BY: Geological Engineer: Petroleum Engineer: ______ Director: OK Cost APPROVAL LETTER: Bond Required: Survey Plat Required: / / 0.K. Rule C-3 Order No.____ Rule C-3(c), Topographic Exception/company owns or controls acreage within a 660' radius of proposed site Plotted on Map Lease Designation Jed Approval Letter Written / 7/

#1

October 10, 1979

Southland Royalty Company P.O. Vrawer 570 Farmington, New Mexico 87401

> Re: Well No. Burr Desert #1 Sec. 24, T. 30S, R. 12E., Wayne County, Utah

Insofar as this office is concerned, approval to drill the above referred to oil well is hereby granted in accordance with Rule C-3, General Rules and Regulations and Rules of Practice and Procedure.

Should you determine that it will be necessary to plug and abandon this well, you are hereby requested to <u>immediately</u> notify one of the following:

MICHAEL T. MINDER Geological Engineer Office: 533-5771 Home: 876-3001 FRANK M. HAMNER Chief Petroleum Engineer Office: 533-5771 Home: 531-7827

Enclosed please find Form OGC-8-X, which is to be completed whether or not water sands (acquifers) are encountered during drilling. Your cooperation in completing this Form will be appreciated.

Further, it is requested that this Division be notified with 14 hours after drilling operations commence, and that the drilling contractor and rig number be identified.

The API number assigned to this well is 43-055-30026.

Sincerely,

DIVISION OF OIL, GAS AND MINING

Michael T. Minder Geological Enginer

/b.tm

cc: USGS



UNITED STATES

(Other instructions on reverse side)

	\checkmark / \checkmark	
Form Budget	approved. Bureau No.	42-R1425.

.	DEPARTMEN	IT OF THE I	NIER	RIOR		5. LEASE DESIGN	ATION AND SERIAL NO.
	GEOL	OGICAL SURV	EY			USA-U-132!	52
	N FOR PERMIT	TO DRILL, I	DEEPE	N, OR PLUG	BACK	6. IF INDIAN, ALI	LOTTER OR TRIBE NAME
1a. TYPE OF WORK b. TYPE OF WELL	RILL 🗵	DEEPEN !		PLUG BA	ak 🗆	7. UNIT AGREEM	ENT NAME
on G	GAS OTHER			NGLE X MULTI	PLB [8. FARM OR LEAS	E NAME
2. NAME OF OPERATOR						BURR DESEI	য্য
	nd Royalty Compa	any				9. WELL NO.	
3. ADDRESS OF OPERATOR	rawer 570, Farm	ington. New	Mexic	∞ 87401 à		#1 10. FIELD AND PO	OOL OR WILDCAS
	Report location clearly an	•		r X -	<u> </u>		
At surface	JL & 750' FEL			195.4.4.131		Unnamed Fi	., OR BLK.
At proposed prod. so:				NOV 28	9(\$	AND SURVEY	OR AREA
San						Sec. 24, 1	
	AND DIRECTION FROM NEA	_		e e		12. COUNTY OR PA	J _
18.7 mil	es southeast of	<u>Hanksville</u>	e, Uta	OF ACRES IN LEASE	. K 4 2 NO 6	Wayne	Utah
LOCATION TO NEARES PROPERTY OR LEASE	T	1990'	10	2560	TO T	160	
(Also to nearest dri 18. DISTANCE FROM PROI			19. PRO	POSED DEPTH		RY OR CABLE TOOLS	
	RILLING, COMPLETED,	N/A		6700		Rotary	
21. ELEVATIONS (Show wh	ether DF, RT, GR, etc.)			•		22. APPROX. DAT	E WORK WILL START
5165' GF	₹					October 1	5, 1979
23.]	PROPOSED CASIN	G AND	CEMENTING PROGRA	A.M		
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FO	ют	SETTING DEPTH	1	QUANTITY OF C	EMENT
17 1/2"	13 3/8" New	48#,H-40,S		200	235 sx	Cl B w/3%	CaCl ₂
12 1/4"	*8 5/8" New	24#,K-55,S		3000'	325 sx	Cl B w/add	<u>itivės – 13 </u>
7 7/8"	5 1/2" New	14#,K-55,S	T&C	6700'	900 sx	C1 B 50/50	Poz w/adds.
Log BOP C Run logs Run logs	1/2" surface ho hecks in daily and run 8 5/8" and run 5 1/2" logs as needed	drilling re casing only casing if p	eports if l produc	s and drill 12 lost circulation ctive.	1/4" h on has	ole to 3000 occured.	good recurns
B" The Ten-P C" The Blowo D" The Multi E&E _l " Access F" Radius Ma	and Elevation F oint Compliance ut Preventer Di -Point Requirem Road Map Into p of Field	e Program agram ments for A. Location	P. D).	tation ng Prog	Plan ram Layout	
G" Drill Pad	Layout & Cut -	Fill Section	on, P	roduction Faci	ilities		
	PROPOSED PROGRAM: If p drill or deepen directions	lly, give pertinent	data on		d measured	and true vertical d	epths. Give blowout
(This space for Feder	al or State office use)					•	
PERMIT NO		-		PPROVAL DATE	_		
APPROVED BY	Sgd.) E. W. Gl	JY NN 		ISTRICT ENGINE	EES	DATE NO	N 20 1979
CONDITIONS OF APPROVA	u, ir ant: cont of Mahural Ro	TO TROPS		0011515			•

State of Utah, Department of Na Division of Oil, Gas, and Missing

CONDITIONS OF APPROVAL ATTACHED

*See Instructions On Reverse Side OPERATOR'S COPY Sait Lake City, Utah 84116 NOTICE OF APPROVAL

OR: South	et engineer, oscilleral evaluation thland Royalty SE 2 NE 2 section continues the continues to the continues the conti	Compan	y . <u>30</u> S ,	<u> </u>	VELL NO. Rum Des		·
atigraphy:	Moenkopi	1240 1530 1825 2260 2275	+3925 +3635 + 3340 +2905		Elephant Canyon Pennsylvanian Tsmay Paradox Molas Mississiffian Devonian Nic Crodien	37 10 4250 4600 4725 5340 5460 6110	+ 565 + 440 - 175 - 295
sh Water:	Operator cytects	WRD ref	out from der in th	n sec 4. ne Navajo	; T.305.; R.138	E.	

itional Logs Needed: Att logging program operats to be adequate.

ential Geologic Hazards:

AW. 11 in sec 34; T. 505; R.13E.

recovered from a core in the fennsylvanian. Sulfur water recovered from the well. No actual H_S gus has been reported. rences and Remarks: 112.7.2. Lie SLC Utah

ure: J. Vaul Mathener

Date: 10 -15 - 79

(D-30-13)4 dcc/b

Depths of fresh-water zones:

57.

Mountain Fuel Supply Co., Dirty Devil Unit No. 1, Wildcat 2,090' fel, 660' fsl, sec. 4, T.30 S., R.13 E., SLB&M, Wayne Co., Utah Elev. 5,293 ft, proposed depth 6,500 ft

Tops, approx.	Quality of water
surface	(dry)
40 ft	(dry but permeable)
630	(dry)
890	(dry but permeable)
1, 180	(dry)
1, 500	useable(?)
1, 560	saline
2,050	saline
2,460	saline
2,580	saline
3,480	brine .
4, 280	brine
5,330	brine
5,620	brine
5,800	brine
	surface 40 ft 630 890 1,180 1,500 1,560 2,050 2,460 2,580 3,480 4,280 5,330 5,620

There are no water wells of record in the near vicinity of the proposed test. Formations of the Glen Canyon Group are dry at this location. However, they dip gently northwestward toward areas where the Navajo and Wingate Sandstones are known to be aquifers of fresh water. Useable water may be present in the Shinarump Member, but deeper aquifers contain saline water or brine at this location.

USGS - WRD 6-29-71

United States Department of the Interior Geological Survey 2000 Administration Bldg. 1745 West 1700 South Salt Lake City, Utah 84138

Usual Environmental Analysis

Lease No.: U-12352

Operator, Southland Royalty Company

Well No.:1

Location: 1990' FNL & 750' FEL Sec.: 24 T.: 30S. R.: 12E.

County: Wayne

State: Utah

Field: Unnamed

Status: Surface Ownership: Public Minerals: Federal

Joint Field Inspection Date: October 25, 1979

Participants and Organizations:

Bob Fieldler

Southland Royalty Co.

Ken Kramme

Century Resources (Archaeologist)

Larry Gearhart

BLM-Hanksville

Jim Boulden

Boulder Contractors

Don Englishman

USGS

Related Environmental Analyses and References:

(1) Unit Resource Analysis, Henry Mountain Planning Unit, BLM, Hanksville, Utah

Analysis Prepared by: Donald Englishman and

Environmental Scientist

George Diwachak

Environmental Scientist

Durango, Colorado

Salt Lake City, Utah

Date: November 13, 1979

Proposed Action:

On October 4, 1979, Southland Royalty Co. filed an Application for Permit to Drill the No. 1 exploratory well, a 6700 ft. oil test of the Pennsylvanian and Devonian Formations; located at an elevation of 5165 ft. in the SE½ NE½ Section 24, T. 30S., R. 12E. on Federal mineral lands and public surface; lease No. U-12352. There was no objection raised to the wellsite nor to the access road.

A rotary rig would be used for the drilling. An adequate casing and cementing program is proposed. Fresh-water sands and other mineral-bearing formations would be protected. A Blowout Preventor would be used during the drilling of the well. The proposed pressure rating should be adequate. Details of the operator's NTL-6 10-Point Subsurface Plan are on file in the USGS District Office in Salt Lake City, Utah and the USGS Northern Rocky Mountain Area Office in Casper, Wyoming. The 13-Point Surface Protection Plan is on file in the District Office in Salt Lake City.

A working agreement has been reached with the BLM, the controlling surface agency. Rehabilitation plans would be decided upon as the well neared completion; the Surface Management Agency would be consulted for technical expertise on those arrangements.

The operator proposes to construct a drill pad 300 ft. wide by 300 ft. long including a reserve pit. No new access road would be constructed; however, approximately 25 miles of access road averaging 18-20 ft. in width would need to be reconstructed from a maintained road. The operator proposes to construct production facilities on disturbed area of the proposed drill pad.

If production is established, plans for a gas flow line would be submitted to the appropriate agencies for approval. The anticipated starting date is upon approval and duration of drilling activities would be about 30 days.

Location and Natural Setting:

The proposed drill site is approximately 19 miles Southeast of Hanksville, Utah, the nearest town. A poor road runs to the location. This well is a Wildcat.

Topography:

The topography in the vicinity of the test site is a stalulized sand dune with a slightly rolling surface. The site is located in the extreme Western edge of the Paradox Basin of Southeastern Utah.

Geology:

The surface geology is the Entrada Formation.

The soil is sand.

No geologic hazards are known near the drillsite.

Seismic risk for the area is minor. Anticipated geologic tops are filed with the 10-Point Subsurface Protection Plan.

Approval of the proposed action would be conditioned that adequate and sufficient electric/radioactive/density logging surveys would be made to locate and identify any potential mineral resources. Production casing and cementing would be adjusted to assure no influence of the hydrocarbon zones through the well bore on these minerals. In the event the well is abandoned, cement plugs would be placed with drilling fluid in the hole to assure protection of any mineral resources.

The potential for loss of circulation would exist. Loss of circulation may result in the lowering of the mud levels, which might permit exposed upper formations to blow out or to cause formation to slough and stick to drill pipe. A loss of circulation would result in contamination due to the introduction of drilling muds, mud chemicals, filler materials, and water deep in to the permeable zone, fissures, fractures, and caverns within the formation in which fluid loss is occurring. The use of special drilling techniques, drilling muds, and lost circulation materials may be effective in controlling lost circulation.

A geologic review of the proposed action has been furnished by the Area Geologist, U.S. Geological Survey, Salt Lake City, Utah.

The operator's drilling, cementing, casing and blowout prevention programs have been reviewed by the Geological Survey engineers and determined to be adequate.

Soils:

No detailed soil survey has been made of the project area. The top soils in the area are snads. The soil is not readily subject to runoff from rainfall and has a slow runoff potential and sediment production would be low. The soils are mildly to moderately alkaline and support the salt-desert shrub

Top soil would be removed from the surface and stockpiled. The soil would be spread over the surface of disturbed areas when abandoned to aid in rehabilitation of the surface. Rehabilitation is necessary to prevent erosion and encroachment of undesired species on the disturbed areas. The operator proposes to rehabilitate the location and access roads per the recommendations of the Bureau of Land Management.

Approximately 8 acres of land would be stripped of vegetation. This would increase the erosional potential. Proper construction practice, construction of water bars, reseeding of slope-cut area would minimize this impact.

Air:

No specific data on air quality is available at the proposed location. There would be a minor increase in air pollution due to emissions from rig and support traffic engines. Particulate matter would increase due to dust from travel over unpaved dirt roads. The potential for increased air pollution due to leaks, spills, and fire would be possible.

Relatively heavy traffic would be anticipated during the drillingoperations phase, increasing dust levels and exhaust pollutants in the area. If the well was to be completed for production, traffic would be reduced substantially to a maintenance schedule with a corresponding decrease of dust levels and exhaust pollutants to minor levels. If the project results in a dry hole, all operations and impact from vehicular traffic would cease after abandonment. Due to the limited number of service vehicles and limited time span of their operation, the air quality would not be substantially reduced.

Toxic or noxious gases would not be anticipated.

Precipitation:

Annual rain fall should range from about 6 to 8" at the proposed 1 ocation. The majority of the numerous drainages in the surrounding area are of a non-perennial nature flowing only during early spring runoff and during extremely heavy rain storms. This type of storm is rather uncommon as the normal annual precipitation is around 7".

Winds are medium and gusty, occurring predominately from West-Southwest to East-Northeast. Air mass inversions are rare. The climate is semiarid with abundant sunshine, hot summers and cold winters with temperature variations on a daily and seasonal basis.

Surface Water Hydrology:

The location is within the Dirty Devil Drainage of the Colorado River Basin. There are no line streams in the vicinity of the proposed well. A dry wash is located Northeast of the location.

Some additional erosion would be expected in the area since surface vegetation would be removed. If erosion became serious, drainage systems such as water bars and dikes would be installed to minimize the problem. The proposed project should have minor impact on the surface water systems. The potentials for pollution would be present from leaks or spills. The operator is required to report and clean-up all spills or leaks.

- Ground Water Hydrology:

Some minor pollution of ground water systems would occur with the introduction of drilling fluids (filtrate) into the aquifer. This is normal and unavoidable during rotary drilling operations. The potential

for communication, contamination and comingling of formations via the well bore would be possible. The drilling program is designed to prevent this. There is need for more data on hydrologic systems in the area and the drilling of this well may provide some basic information as all shows of fresh water would be reported. Water production with the gas would require disposal of produced water per the requirements of NTL-2B. The depths of fresh water formations are listed in the 10-Point Subsurface Protection Plan. The pits would be unlined unless soil conditions do not provide a tight stable pit. If fresh water should be available from the well, the owner or surface agency may request completion as a water well if given approval.

Vegetation:

Vegetation in the area consists mainly of blackbrush, broom snakeweed, indian rice grass, galleta grass, Mormon tea, four wing saltbush, cacti and annuals.

Plants in the area are of the salt-desert-shrub.

Proposed action would remove about 8 acres of vegetation. Removal of vegetation would increase the erosional potential and there would be a minor decrease in the amount of vegetation available for grazing.

The operator proposes to rehabilitate the surface upon completion of operations.

<u>Wildlife</u>:

The fauna of the area consists predominantly of antelope, desert bighorn sheep, coyotes, rabbits, foxes, and varieties of small ground squirrels and other types of rodents and various types of reptiles. The area is used by man for the primary purpose of grazing domestic livestock and sheep. The birds of the area are raptors, finches, ground sparrows, magpies, crows, jay, and seasonal species.

An animal and plant inventory has been made by the BLM. No endangered plants or animals are known to inhabit the project area.

Social-Economic Effect:

An on the ground surface archaeological reconnaissance would be required prior to approval of the proposed action. Appropriate clearances would then be obtained from the surface managing agency. If a historic artifact, an archaeological feature or site is discovered during construction operations; activity would cease until the extent, the scientific importance, and the method of mitigating the adverse effects could be determined by a qualified cultural resource specialist.

There are mp occupied dwellings or other facilities of this nature in the general area. Minor distractions from aesthetics would occur over the lifetime of the project and is judged to be minor. All permanent facilities placed on the location would be painted a color to blend in with the natural environment. Present use of the area is grazing, recreation, and oil and gas activities.

Noise from the drilling operation may temporarily disturb wildlife and people in the area. Noise levels would be moderately high during drilling and completion operations. Upon completion, noise levels would be infrequent and significantly less. If the area is abandoned, noise levels should return to pre-drilling levels.

The site is not visible from any major roads. After drilling operations, completion equipment would be visible to passersby of the immediate area but should not present a major intrusion.

The economic effect on one well would be difficult to determine. The overall effect of oil and gas drilling and production activity are significant in Wayne County.

But should this well discover a significant new hydrocarbon source, local, state, and possible national economics might be improved. In this instance, other development wells would be anticipated, with substantially greater environmental and economic impacts.

Should the wellsite be abandoned, surface rehabilitation would be done according to the surface agency's requirements and to USGS's satisfaction. This would involve leveling, contouring, reseeding, etc., of the location and possibly the access road. If the well should produce hydrocarbons, measures would be undertaken to protect wildlife and domestic stock from the production equipment.

There are no national, state, or local parks, forests, wildlife refuges or ranges, grasslands, monuments, trails or other formally designated recreational facilities near the proposed location.

The proposed location is within the Henry Mountain Planning Unit. This Environmental Assessment Record was compiled by the Bureau of Land Management, the surface managing agency of the Federal surface in the area. The study includes additional information on the environmental impact of oil and gas operations in this area and gives land use recommendations. The E.A.R. is on file in the agency's State offices and is incorporated herein by reference.

Waste Disposal:

The mud and reserves pits would contain all fluids used during the drilling operations. A trash pit would be utilized for any solid wastes generated at the site and would be buried at the completion of the operations. Sewage would be handled according to State sanitary codes. For further information, see the 13-Point Surface Plan.

Alternative to the Proposed Action:

(1) Not approving the proposed permit-The oil and gas lease grants the lessee exclusive right to drill for, mine, extract, remove and dispose of all oil and gas deposits. Under leasing provisions, the Geological Survey has an obligation to allow mineral development if the environmental consequences are not too severe or irreversible. Upon rehabili-

tation of the site, the environmental effects of this action would be substantially mitigated, if not totally annulled. Permanent damage to the surface and subsurface would be prevented as much as possible under USGS and other controlling agencies supervision with rehabilitation planning reversing almost all effects. Additionally, the growing scarcity of oil should be taken into consideration. Therefore, the alternative of not proceeding with the proposed action at this time is rejected.

(2) Minor relocation of the wellsite and access road or any special, restrictive stipulations or modifications to the proposed program would not significantly reduce the environmental impact. There are no severe vegetative, animal or archaeological-historical-cultural conflicts at the site. Since only a minor impact on the environment would be expected, the alternative of moving the location is rejected. At abandonment, normal rehabilitation of the area such as contouring, reseeding, etc., would be undertaken with an eventual return to the present status as outlined in the 13-Point Surface Plan.

Mitigative Measures:

Drilling should be allowed provided the following mitigative measures are incorporated into the proposed APD and adhered to by the operator.

A. The reserve pit should be lined if soil conditions do not provide a tight, sable pit.

Adverse Environmental Effects Which Cannot Be Avoided:

Surface disturbance and removal of vegetation from approximately 8 acres of land surface for the lifetime of the project which would result in increased and accelerated erosional potential. Grazing would be eliminated in the disturbed areas and there would be a minor and temporary disturbance of wildlife and livestock. Minor induced air pollution due to exhaust emissions from rig engines of support traffic engines would occur. Minor increase in dust pollution would occur due to vehicular traffic associated with the operation. If the well is a gas producer, additional surface disturbance would be required to install production pipelines. The potential for fires, gas leaks, and spills of oil and water would exist. During the construction and drilling phases of the project, noise levels would increase. Potential for sub-surface damage to fresh water aguifers and other geologic formations exists. Minor distractions from aesthetics during the lifetime of the project would exist. If the well is a producer, an irreplaceable and irretrievable committment of resources would be made. Erosion from the site would eventually be carried as sediment in the Colorado River. The potential for pollution to the Dirty Devil River would exist through leaks and spills.

Determination:

11/19/79

This requested action <u>does not constitute</u> a major Federal action significantly affecting the environment in the sense of NEPA, Section 102 (2) (C).

Date

Di

District Engineer (U.S. Geological Survey Conservation Division Oil and Gas Operations Salt Lake City District

DIVISION OF UIL, GAS AND MINING

cc: USGS

SPUDDING INFORMATION

NAME OF COMPANY: Southland Royalt	y Company
WELL NAME: Burr Desert Unit #1	
SECTION 24 SE NE TOWNSHIP 30S	RANGE 12E COUNTY Wayne
DRILLING CONTRACTOR	
RIG #	
SPUDDED: DATE 11/29/79	
TIME 4:00 p.m.	
How rotary	
DRILLING WILL COMMENCE ASAP	-
REPORTED BY	
TELEPHONE #	
DATE December 6, 1979	SIGNED May Munden

UN D STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	-	
5. L;E U~12352	- : 1	

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TE	RIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME	· .
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME	2
1. oil XX gas other other	Burr Desert 9. WELL NO.	· · ·
2. NAME OF OPERATOR	1	
Southland Royalty Company	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Unnamed Field	
P.O. Drawer 570, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AN	ID SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	
below.) AT SURFACE: 1990' FNL & 750' FEL	Section 14, T30S, F	
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. S	
AT TOTAL DEPTH:	Wayne Uta	<u></u>
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	14. API NO.	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, K	DR AND WD)
	5165' GR	DB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3103 di	
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE CREPAIR WELL CPULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES SHANDON* Other) REVISED Casing & Cement Program	(NOTE: Report results of multiple co change on Form 9–330.)	mpletion or zone
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertinent REVISED CASING PROGRAM:	rectionally drilled, give subsurface	ertinent dates, locations and
TETTOET ONOTHE TROUBER.		
Size of Hole Size of Casing Weight/Foot	Setting Depth	Quantity of Cmt
17-1/2" 13-3/8" 48#	200'	235 sacks
12-1/4" 9-5/8" 32.30# & 36	S# 2900'	600 sacks
7_7/8" 5_1/2" 14#	6700'	900 sacks
APPROVED BY THE DIVI	SIONI OF	
OIL, GAS, AND MINING	SICH OF	
DATE: 1-21-80		
BY: when an assessment commencer were	and the same of th	•
ubsurface Safety Valve: Manu. and Type	Set @	Ft.
8. I hereby certify that the foregoing is true and correct		
Dist Prod Ma	r Date January 14, 19	980
	S11515	
(This space for Federal or State office		
PPROVED BY TITLEONDITIONS OF APPROVAL, IF ANY:	JAN .	1 7 1980

Dec. 1973	Budget Bureau No. 42-K1424
UNI. D STATES	5. LL.5E
DEPARTMENT OF THE INTERIOR	U-12352
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas under other	Burr Desert 9. WELL NO.
2. NAME OF OPERATOR	1
Southland Royalty Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Unnamed Field
P. O. Drawer 570, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
helow)	Section 14, T30S, R12E
AT SURFACE: 1990' FNL & 750' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	<u>Wayne</u> Utah
AT TOTAL DEPTH:	14. API NO.
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	<u> </u>
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5165' GR
TEST WATER SHUT-OFF	
REPAIR WELL \(\bar{\Bar}\) \(\bar{\Bar}\) \(\bar{\Bar}\)	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
HULTIPLE COMPLETE	
other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent	all pertinent details, and give pertinent dates, rectionally drilled, give subsurface locations and to this work.)*
1-14-80 Ran 66 joints of 9-5/8", 32.30# & 36#, Cemented with 500 sacks of Class "B" 50 flake per sack and 10# Kolite per sack. Class "B" with 2% CaCl2 and 1/4# gel fl	H-40 & K-55 casing set at 2890'. /50 Poz with 6% gel, 1/4# gel Followed by 100 sacks of
released ahead of slurry. Casing was p slurry was still inside casing. Pressu pipe was split. Set slips, cut off cas	ressured up to 3000 psi while re broke back to 0 psi. Suspect
, , , , , , , , , , , , , , , , , , , ,	2.

(SEE OTHER SIDE).....

Subsurface Safety Va	Ive: Manu. and Type	Set @ Ft.
18. I bereby certify th	nat the foregoing is true and correct	
SIGNED	Many TITLE Dist. Prod. Mgr.	DATE JANUARY 21 1980
-	(This space for Federal or State office us	se)
APPROVED BYCONDITIONS OF APPRO	VAL, IF ANY:	DATE JAN 24 1980

DIVISION OF OIL, GAS & MINING

went in hole with 8-3/4" bit. Tagged cement at 1207'. Cleaned out to float coccar.

float collar. No cement under float collar.

Cleaned out to 2890'. Picked up RTTS packer.

Located split in 9-5/8" between 1150' and 1300'.

Set RTTS at 2800'. Established Rate of 7BPM

at 1000 psi around shoe. No circulation to at 1207'. Cleaned out to bloat collar. Drilled surface.

1-16-80

Set cement retainer at 2792'. Cemented shoe with 225 sacks of Class "B" w/2% CaCl2 & 1/4# flocele/sx. Top of Cement by temperature survey at 2400'.

1-17-80

Set RTTS at 1040'. Cemented split with 225 sacks of Class "B" with 2% CaCl2. Wait on cement 4 hours. Would not hold pressure. Re-cemented with 200 sacks of Class "B" with 2% CaCl2. Squeezed to 1000 psi with 3 bbls slurry displaced. WOC 4 hours. Test to 1000 psi. Held OK.

o 1-18-80 Drilled cement from 1057' to 1207'. Pressure tested to 1000#/30 minutes.

1-19-80

Drilled cement retainer. Pressure tested to 600 psi/30 minutes.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State of addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present sign fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, betwee above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date w conditioned for final inspection looking to approval of the abandonment.

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands in such State, pursuant to applicable State law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

in accordance with Federal requirements. Consult

be described

or Indian land should

Item 4: If there are no applicable State requirements, locations on Federal State or Federal office for specific instructions.

UNITED STATES DEPARTMENT OF THE INTERIO. GEOLOGICAL SURVEY

(FORM 9-329) (2/76) OMB 42-RO 356

MONTHLY REPORT
OF
OPERATIONS

Lease No	43-012352									
Communitization	on Agreeme.it No.									
Field Name	Unnamed									
Unit Name										
Participating A	rea									
County	Wayne	StateUtah								
	perator Southland Royalty Company									
☐ Amended Re	port WELL NAME	Burr Desert								

The following is a correct report of operations and production (including status of all unplugged wells) for the month of January , 19 80

(See Reverse of Form for Instructions)

This report is required by law (30 U.S.C. 189, 30 U.S.C. 359, 25 U.S.C. 396 d), regulation (30 CFR 221.60), and the terms of the lease. Failure to report can result in the assessment of liquidated damages (30 CFR 221.54 (j)), shutting down operations, or basis for recommendation to cancel the lease and for feit the bond (30 CFR 221.53).

Well No.	Sec. & 1/4 of 1/4	TWP	RNG	Well Status	Days Prod.	*Barrels of Oil	*MCF of Gas	*Barrels of Water	Remarks
*1 yA	24 SENE	30S	12E	DRG					Drilling.
								FEB 1 9 198	
								DIVISION O	

*If none, so state.

DISPOSITION OF PRODUCTION (Lease, Participating Area, or Communitized Area basis)

	Oil & Condensate	Gas	Water
	(BBLS)	(MCF)	(BBLS)
*On hand, Start of Month		xxxxxxxxxxxxxx	xxxxxxxxxxxxxxxxx
*Produced			
*Sold			xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
*Spilled or Lost		XXXXXXXXXXXXXXXX	xxxxxxxxxxxxxxxx
Flared or Vented	xxxxxxxxxxxxxxxx		xxxxxxxxxxxxxxx
*Used on Lease			xxxxxxxxxxxxx
Injected			
Surface Pits	xxxxxxxxxxxxxxxx	xxxxxxxxxxxxxx	
Other (Identify)			
On hand, End of Month		xxxxxxxxxxxxxxx	XXXXXXXXXXXXXXXX
API Gravity/BTU Content			XXXXXXXXXXXXXXX
Authorized Signature:	Lyan Address:	P. O. Drawer 570, 1	
Title: District Production Manager		Page One of O	ne 87401

DIVISION OF OIL, GAS AND MINING

PLUGGING PROGRAM

NAME OF COMPANY:_	Southland	Royalty	Kirk Tarso	ns 505-325-1	841)
WELL NAME: BU	vr Desert Unit	#1			
SECTION 24 SE NE	TOWNSHIP_30S	RANGE	12E	COUNTY Wa	yne
VERBAL APPROVAL GI	VEN TO PLUG TH	E ABOVE REF	ERRED TO WE	ELL IN THE FO	DLLOWING
TOTAL DEPTH: 6880) *				
CASING PROGRAM:			FORMATION	TOPS:	
13 3/8" @ 214"			Navajo	400'	Elephant Canyon
casing split at 11			Kayenta	940'	Pennsylvanian
squeezed (TOC 80			Wingate	1250'	Ismay
9 5/8" @ 2890' (TO			Chinle	1530'	Paradox
8 3/4" openhole 45			Moenkopi	1860'	Molas
7 7/8" openhole TD			White Rim	2360'	Mississippian
			Organ Rock	2830'	Devónian
PLUGS SET AS FOLLO	WS:		Cedar Mesa	2877'	Elbert
#1 5700' - 6050'	125 sx				
#2 4800' - 5000'	60 sx				
#3 3800' - 4000'	70 sx				
#4 2800' - 3000'	75 sx				
#5 900' - 1250'	130 sx				•
#6 150' - 250'	35 sx				
Braden head squeez	e 85 sx				
#7 surface - 30' DATE February	10 sx ary 18, 1980	\$10	NED Origin	nai Signed By M. T. M	inder

cc: USGS

TLABORATORY, INC. SAN JUAN TESTIN

Farmington, New Mexico 87401 (505) 327-4966

736 Sixth Street Durango, Colorado 81301 (303) 247-5766

Bu. X DESERT #1

4,200

87.5

Southland Royalty Company PO Drawer 570

40020

Client

Farmington, New Mexico

87401

981-171 Job No.

311-00054 Lab./Invoice No.

February 14, 1980 Date of Report

DST #1 Project Sampled By Southland Royalty Co. 2/13/80 Unknown Location _ 6110' Submitted By Mr. Fielder 2/13/80 6088 Well Head Source of Material Authorized By Mr. Fielder 2/13/80

WATER ANALYSIS FOR PETROLEUM ENGINEERING

<u>Constitutents</u> .	Test Results	Constitutents		
Total Dissolved	Soilds 25, 203 mg/L	Cations	meq/L	mg/L
Н̄q	6.7	Sodium	325.7	7,49
Specific Gravity	1.019 at 72°F	Calcium	67.6	1,35
Resistivity	0.238 ohm/meter at 25°C	Magnesium	29.0	. 354
Conductivity	42,000 micromhos/ cm at 25°C			
Comments		Anions -		
	vere hydrated iron oxide	Chloride	325.2	11,513
with some mud.		Bicarbonate	9.6	586
	•	Carbonate	0	0 -



DIVISION OF OIL, GAS & MINING

Copies to:

Client (3) Attn: Mr. Fielder Respectfully submitted,

Hydroxide

Sulfate

SAN JUAN TESTING LABORATORY

form 9-331 Dec. 1973		et Bureau No. 42-R14
UN D STATES DEPARTMENT OF THE INTERIOR	5. \SE 2.555.50 U-12352 \$ 5.55.50	2. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE	OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT N	T + +
1. oil gas other other	8. FARM OR LEASE NAM Burr Desert 3 5	ME gg, company
2. NAME OF OPERATOR	9. WELL NO.	
Southland Royalty Company	10. FIELD OR WILDCAT N	IAME :
3. ADDRESS OF OPERATOR	<u>U</u> nnamed	
P.O. Drawer 570, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	* * **
below.) AT SURFACE: 1990' FNL & 750' FEL	Section 24, T30	
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH Wayne	Utah
AT TOTAL DEPTH:	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW 5165' GR	DF, KDB, AND W
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)	(NOTE: Report results of mul change on Form 9-3	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dir measured and true vertical depths for all markers and zones pertinent	ectionally drilled, give subs	give pertinent dates urface locations an
2-21-80 Spotted plugs as follows:		
#1 125 sacks Neat from 6050'-570 #2 60 sacks Neat from 5000'-480		*• ;
#3 70 sacks Neat from 4000'-380		
#4 75 sacks Neat from 3000'-280		
#5 130 sacks Neat from 1250'- 90		
#6 35 sacks Neat from 250'- 15		1
#7 85 sacks neat down 9-5/8" X		
10 sacks of cement at surfac	e.	
Installed dry hole marker. Final clean up will be made at a	later date	
·		• .
ubsurface Safety Valve: Manu. and Type	Set @	Ft

18. I hereby certify that the foregoing is true and correct TITLE Dist. Prod. Mgr. DATE March 3, 1980

APPROVED BY ________ CONDITIONS OF APPROVAL, IF ANY:

MAR 1 0 1980

*See Instructions on Reverse Side

DIVISION OF OIL, GAS & MINING

UNITED STATES DEPARTMENT OF THE INTERIOR

			.:.	Buc	get i	Bureau	No. 42-	R1424
	5.	LEASE	`_	_ ··	-	.:	F 12	
		<i>U-1235</i> 2	- '	:		÷.	3.5	
	6.	IF INDIAN,	ALL (OTTE	ΕO	R TRI	BE NAM	E
-					<u>. </u>	ث	1 63 -	
	7.	UNIT AGRE	EME	NT	NAM	IE]-	7 3 -	
nŧ			. ,	1 - 3	;	ذ	7 2 1	
•	8.	FARM OR LI			ME	5	- 2 -	
		Burr Des	er	t"		<u>_</u> :		
	9.	WELL NO.					= -	
۲		1		٠ - ،	:	्	3 E .	
_	10.	FIELD OR W	ΊĻΟ	CAT	NAN	1E		
		Unnamed	-^ .		-	7.	· -	
	11.	SEC., T., R.,	M.,	OR	BLK	. AN	SURVE	Y OR
7.		AREA		(10 mm 1 m	
		Section						
	12.	COUNTY OF	PA	RISĻ	1 1.	3. ST	ATE .	
		Wayne				Uta.	ħ	
ź.	14.	API NO.		, -		3	9 : 3 5	
. 1				÷ .				

	GEOLOGIC	AL SURVEY	6.	IF INDIAN	, ALLOTTE	E OR TR	IBE NAM	Ε
		A. J. To arell					6,	· · · · · · · · · · · · · · · · · · ·
SUNDRY N	OTICES ANI	D REPORTS ON WELLS	7.	UNIT AGE	REEMENT N	AME_	7 1/2	
(Do not use this form	for proposals to dri	Il or to deepen or plug back to a different	<u> </u>		<u> </u>	<u>-i</u>	<u> </u>	
reservoir. Use Form 9-	tor such brob	oosais.)	8.		LEASE NAM	ΛE -	7	
1. oil g	as 🗇				esert			
	ell U othe	<u>r</u>	_ 9.	WELL NO.		<u>=</u>	÷ ; .	
2. NAME OF OPE		ng garantagan sa kabangan sa <u>t</u>	- <u>-</u> -			• • • •	<u> </u>	
Southland R		pany	- 10.	Unname	WILDCAT N	IAME	100	
3. ADDRESS OF					<u> </u>	- -		
		ngton, New Mexico 87401	. 11.	SEC., T., I	R., M., OR E	BLK. AN	ID SURVE	YOR
	WELL (REPORT	LOCATION CLEARLY. See space 17	1		ີ່ວິ. - 3.4 : ຫາ		D 3 1 Tr	
below.) AT SURFACE:	1990' FNL	& 750' FEL			24, T3			
AT TOP PROD			12.		OR PARISH	-	-	
AT TOTAL DEP		in stimble being being	<u> </u>	Wayne		Uta	<u>ah - :</u>	
			14.	API NO.			2	
		INDICATE NATURE OF NOTICE,			7		1 - 1	
REPORT, OR C	THER DATA		15.	ELEVATIO	NS (SHOW	DF, K	DB, AND	WD)
DECLIEST FOR ADD	DOMAL TO:	SUBSECUENT DEPOST OF		5165'	SR _ = =	·		
REQUEST FOR APP	_	SUBSEQUENT REPORT OF:			37.5 %			
TEST WATER SHUT FRACTURE TREAT		片			- 1 1 1 1 1			
SHOOT OR ACIDIZE	, ∃	H						
REPAIR WELL	` H		(N/	OT EcoDonad		. 14: -1		_
PULL OR ALTER C	ASING 🗍	PPROVED BY TH	HE 'O	IVISION	or form 9-	itipie co 330.)	mpletion of	r zone
MULTIPLE COMPLE	=	ML, GAS, AND N	IININ	NG		,		
CHANGE ZONES		□	,			,		
ABANDON*	XX	10 ATE: 3/11/	80			*	<u>:</u>	
(other)			1	/	1	7		
		BY: 11.7.	74	endl	<u> </u>	-		<u>-</u>
including estima	ated date of star	IPLETED OPERATIONS (Clearly state ting any proposed work. If well is di hs for all markers and zones pertinen	rectio	nally drilled	etails, and d, give sub	give pe surface	locations	lates, and
9-5/8" cas	ing set in	17-1/2" hole at 2890'.			~	,		
	e drilled to							
•	e drilled to							
FORMATION _	rops:	•					.'	
Navajo	380 '	Organ Rock	284	-	Barker	Cree	k	5218 '
Kayenta	982 '	Cedar Mesa	300	6 '	Pinker	ton T	rail	5330 '
Wingate	1212'	Elephant Canyon	384	0'	Molas			56 92'
Chinle	1530 '	Pennsylvanian	432	8 '	Missis.	si p pi	an	5826 '
Moenkopi	1888'	Ismay	475	2'	Devonia	an		6674 '
White Rim	2350'	Paradox	490	6 '	${\it Elbert}$	1 .		6738'
		Aka h	507	8 '	McCraci	ken		6804 '
(CONTINUED	OTHER SIDE)				•		
Subsurface Safety Va	alve: Manu. and T	ype			Set (். a <u>∸</u>		_ Ft.
18. I hereby certify t	hat the foregoing	is true and correct		· · · · · · · · · · · · · · · · · · ·	10 b	<u>- </u>	(1.00 to 1.00	
SIGNED	S/an x	Dist. Prod. Me	gr.	DATE Ma	rch 3,	1990	SCI	MV F
	څ څ	(This space for Federal or State offic	e use)		្នៃ ១ គឺ ។ នៃក្រី ។	THE		
APPROVED BY		TITLE		_ DATE	25. 4 11. 4 11. 5 11. 5		MINT 1	0 1980
CONDITIONS OF APPRI	OVAL, IF ANY:					-i. :	Millian	

(,)

UNITED ST _S DEPARTMENT OF THE INTERIOR William Charles 200

ر د . 1

...

. .

300 18HC

C. IF INCIAN,	ME SUBSTITUTION OF OF
LESSON THUS POT	Plugs as follows: SUNDRY MOTICES AND REPORTS ON WELLS
#1 290 TILE#2 290 TILE#3 #4 #5 #6 #7	125" sacks Neat from 6050'-5700' 60 sacks Neat from 5000'-4800' 70 sacks Neat from 4000'-3800' 130 sacks Neat from 1250'-900' 35 sacks Neat from 250'-157' 85 sacks Neat down 9-5/8" X 13-3/8" annulus.
	10 sacks of Neat at surface. Install dry hole marker.
(VER	BAL APPROVAL BY E.W. GUYNN ON 2-17-80)
- , ;	

Company of the control of the contro

General: This form is designed for concerning the use of this form and the superal concerning the use of this form and spursons. Any necessary special instructions concerning the use of this form and spursons. Any necessary special instructions concerning the use of this form and spursons. Any necessary special instructions concerning the use of the same of the sa

 Little Stellag to the Att 3 a + 12 2-47

1.00

et i benevañ no ent mait e es.

Vin zete

· SV VISIES COSTILORIOS

CANTAL TO CONTRACT

UNITED STATES DEPARTMENT OF THE INTERIC GEOLOGICAL SURVEY

(FORM 9-329) (2/76) MB 42-RO 356

MONTHLY REPORT OF OPERATIONS

Lease No	43-012352	N	
Communitizat	ion Agreer t No		
Unit Name			
County	Wayne	State <u>Utah</u>	
Operator	Southland Roy	valty Company	
☐ Amended R	eport WEIL NAME	Burr Desert	

The following is a correct report of operations and production (including status of all unplugged wells) for the month of FEBRUARY 19 80

(See Reverse of Form for Instructions)

This report is required by law (30 U.S.C. 189, 30 U.S.C. 359, 25 U.S.C. 396 d), regulation (30 CFR 221.60), and the terms of the lease. Failure to report can result in the assessment of liquidated damages (30 CFR 221.54 (j)), shutting down operations, or basis for recommendation to cancel the lease and for feit the bond (30 CFR 221.53).

Well No.	Sec. & '4 of '4	TWP	RNG	Well Status	Days Prod.	*Barrels of Oil	*MCF of Gas	*Barrels of Water	Remarks
1	24 SENE	3 0 S	12E	P&A					Drilled To TD 6880'.
							DEGE MAR 2	11 V EII 6 1980	
						: ::	DIVIS OIL, GAS	ION OF 8 & MINING	

*If none, so state.

DISPOSITION OF PRODUCTION (Lease, Participating Area, or Communitized Area basis)

	Oil & Condensate		Gas		Wat	er .
	(BBLS)		(MCF)		(BBL	.S)
*On hand, Start of Month		xxxx	(XXXXXXX	(XXXX)	xxxxxxxx	xxxxxxx
*Produced						
*Sold					xxxxxxxx	xxxxxxx
*Spilled or Lost		XXXX	XXXXXXX	XXXXX	XXXXXXXX	xxxxxxx
*Flared or Vented	XXXXXXXXXXXXXXXX				XXXXXXXX	xxxxxxx
*Used on Lease					xxxxxxxx	xxxxxxx
*Injected						
*Surface Pits	<u>xxxxxxxxxxxxxxxxxx</u>	XXXX	xxxxxxx	XXXXX		
*Other (Identify)						
*On hand, End of Month	, A	XXXX	xxxxxxx	XXXXX	xxxxxxxxx	(XXXXXX)
*API Gravity/BTU Content	/ 				xxxxxxxxx	xxxxxxx
Authorized Signature: Sim K	Yan Address: _	P. O.	Drawer	570,	Farmington	
Title District Production Manager		Page	One	of	One	87401

May 23, 1980

Southland Royalty
P.O. Drawer 570
Farnington, New Mexico 87401

Re: Well No. Burr Desert #1
Sec. 24, T. 30S, R. 12E.
Wayne County, Utah

Gentlemen:

This letter is to advise you that the Well Completion or Recompletion Report and Log for the above mentioned well is due and has not been filed with this office as required by our rules and regulations.

Please complete the enclosed Form OGC-3, and forward it to this office as soon as possible.

Also, rule C-5, General Rules and Regulations and Rules of Practiaceand Procedure, requires that a well log shall be filed with the Commission together with a copy of the electric and radioactivity logs.

Please forward any logs that were run on the above well together with the Well Completion.

Your prompt attention to the above will be greatly appreciated.

Sincerely,

DIVISION OF OIL, GAS, & MINING

JANICE TABISH CLERK-TYPIST



DIVISION OF

OIL, GAS & MINING

June 9, 1980

State of Utah Division of Oil, Gas, and Mining Ms. Janice Tabish 1588 West North Temple Salt Lake City, UT 84116

Burr Desert #1 RE:

Sec. 24, T39S, R12E

Wayne Cnty, UT

Dear Ms. Tabish:

Attached is a Well Completion or Recompletion Report and log for the above referenced well in accordance with the State of Utah rules and regulations.

In reference to rule C-5, of the General Rules and Regulations and Rules of Practice and Procedure, copies of the electric and radioactivity logs will be sent to you under separate cover by our office in Denver, Colorado.

Thank you for your patience concerning these logs. If I can be of further assistance, please contact me.

Sincerely,

SOUTHLAND ROYALTY COMPANY

Krista Edwards

tal dwards

Secretary to the District Engineer

Attachments

UI TED STATES BEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUBMIT IN DUP TE*

Form approved. Budget Bureau No. 42-R355.

		GEOLOG	ICAL S	URVE	Y		reverse	U-123	352		
WELL CO	OMPLETIO	N OR REC	OMPLE	TION	REPORT	AN	ID LOG	6 IF IN		LOTTEE OR TRIBE NAM	
1a. TYPE OF WE	LL: 0	II. GAS		DRY X	Other			7. UNIT	AGREEME	NT NAME	
b. TYPE OF COI		ELL WEI	.L 🗀	DRY 🗀	Other			_ ``			
NEW WELL		EEP- PLU	G D	ESVR.	Other Plu	g &	<u>Abandon</u>	S. FARM	OR LEAS	E NAME	
2. NAME OF OPERA	TOR	Burr	Burr Desert								
Southland F	Royalty Co	mpany						9. WELL	NO.		
								#1			
P. O. Drawe	r 570, Fa	rmington,	NM 87	401						OL, OR WILDCAT	
4. LOCATION OF WI	ELL (Report loca		Unnamed Wildcat 11. SEC., T., R., M., OR BLOCK AND SURVEY								
1990' FNL &	750' FEL	SE NE						OR A	REA	, OR BLOCK AND SORVE	
At total depth								Secti	on 24	, T30S, R12E	
14. PERMIT NO. DATE ISSUED								12. COUN	12. COUNTY OR 13. STATE PARISH		
				3-055-3		10	-10-79	Wayne	·	Utah	
5. DATE SPUDDED	16. DATE T.D.	REACHED 17.		, ,		. ELE	VATIONS (DF,	RKB, RT, GR, ETC.	19.	ELEV. CASINGHEAD	
11-29-79	2-15-		2-2	2-80 P8	i <u>A</u>		5165' G				
20. TOTAL DEPTH, MD	▲ TVD 21. PI	JUG, BACK T.D., MI	A TVD	22. IF MUI HOW M	TIPLE COMPL.	••	23. INTERV	D BY		CABLE TOOLS	
6880'					Vn mun\d		<u> </u>	0'-688	-	25. WAS DIRECTIONAL	
4. PRODUCING INTE	,	S COMPLETION—	TOP, BOTTO	M, NAME (MU AND TVU)				1	SURVEY MADE	
Not complet	ea								$ _{\mathcal{D}}$	eviation	
6. TYPE ELECTRIC	AND OTHER LOGS	RUN								WAS WELL CORED	
Comp. Neut.	Dens . De	ial latero	loa-SF	L. Bone	ehole Con	np	Sonic. 1	Dual Ind.	У	es	
8.	<i>ve.se</i> , , , ,				ort all strings						
CASING SIZE	WEIGHT, LB	./FT. DEPTH	SET (MD)	но	LE SIZE		CEMEN	TING RECORD		AMOUNT PULLED	
13 3/8"	13 3/8" 48#		214' 17								
9 5/8"	32.3#	289	0'	12	1/4"	64	9 sx (sc	(zd)			
				_							
9.		LINER RECO	D.D.	<u> </u>	.	<u> </u>	30.	TUDING DI	TOOR D		
size	TOP (MD)	BOTTOM (MD)		CEMENT*	SCREEN (M	<u>, , , , , , , , , , , , , , , , , , , </u>	SIZE	TUBING RE		PACKER SET (MD)	
	101 (MD)	BOTTOM (MD)	-		Jewest (M.			-	(MD)	TREEDIN DET (HE)	
			_			—- ·		_			
1. PERFORATION RE	CORD (Interval, a	ize and number)		82.	AC	D, SHOT, FI	RACTURE, CEME	NT SQU	EEZE, ETC.	
					DEPTH INT					MATERIAL USED	
								•			
0.1				- DDCT	NORMAN		1				
3.* ATE FIRST PRODUCT	ION PROI	OUCTION METHOD	(Flowing.		OUCTION	and tu	ne of numn)	l we	LL STATU	s (Producing or	
					•	•	, , , , , , , , , , , , , , , , , , , ,	ENTE PIE	VITT	กลา	
ATE OF TEST	HOURS TESTED	CHOKE SIZ		'N. FOR	OIL-BBL.		GAS-MCF.	0130	BL.	GAS-GL ATIO	
			TEST	PERIOD					1 40		
OW. TUBING PRESS.	CASING PRESSU	RE CALCULATE 24-HOUR R		-BBL.	GAS	MCF.	WA	TER-BBLJUN 1	Long	MAVITY-API (CORR.)	
4. DISPOSITION OF G	AS (Sold, used fo	r fuel, vented, et	c.)		,			DIV!	SION T	3F IINING	
5. LIST OF ATTACH	MENTS					-		OIL, GA	ئننى ن		
		٠									
3. I hereby certify	that the foregoi	ng and attached	informatio	n is compl	ete and corre	ct as	determined f	om all available	records	_ _	
SICNED	In Va	· Loria	m.	TOTAL Di	strict P	rode	uction N	lanager	_{mr} 5.	-30 -80	

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments

should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. "Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

FORMATION	тор	воттом	DESCRIPTION, CONTENTS, ETC.	NAME	тор		
				NAME	MEAS. DEPTH	TRUE VEST. DEPTE	
Navajo	380 '						
Kayenta	982'						
Wingate	1212'						
Chinle	1530'				4		
Moenkopi	1888'						
White Rim	2350 '						
Organ Rock	2840'						
Cedar Mesa	3006'			1	1		
Elephant Canyon	3840'						
pennsylvanian	4328'						
smay	4752'					1	
Paradox	4906'	•					
Akah	5078'						
Barker Creek	5218'						
Pinkerton Trail	5330'						
Molas	5692 '						
Mississippian	5826 '						
Devonian	6674'	•					
Elbert	6738'						
McCracken	6804'			N .			



June 16, 1980

Janice Tabish 1588 W. North Temple Salt Lake City, Utah 84116

Ms. Tabish,

Enclosed are copies of the petrophysical logs run on our Burr Desert #1 well located in Section 24, T30S-R12E, Wayne County, Utah. Please advise if there are any additional requirements of the State of Utah concerning this well. Thank you.


Sincerely,

Robert M. Mason District Geologist

RMM: tmo

Attachments

Robert M. Mason District Geologist Southland Royalty Co. 410 17th Street, Ste. 1000 Denver, Colo. 80202



OIL, CAE & MINING DIVICION OF